


# Technical Bulletin




## ASM's Environmental Systems Workplace® Recycled Materials: FS200 Low Profile Quick-Loc System

Renewed concerns about the environment, and creating and maintaining a greener society, have brought new focus to responsible manufacturing. As manufacturers, ASM is acutely aware of its obligation to incorporate significant content of recycled materials into its products. In our capacity as consumers, it's incumbent upon us to fully exploit the opportunities offered by products containing recycled materials. To help promote more environmentally beneficial practices, the US Green Building Council's LEED (Leadership in Energy and Environmental Design) rating system offers incentives for using material with recycled content, awarding up to 2 points toward LEED certification.



ASM's Environmental Systems Workplace® targets its contribution to 3 of the 5 categories addressed by LEED's standards. One category deals with building materials in terms of recycled content. ASM's FS200 Low Profile Quick-Loc System contains 43.2% recycled material, 11.4% of which is post consumer waste and 31.8% of which is post industrial material.



ASM FS200 panels consist of cementitious fill contained within a steel shell. The steel shell's composition uses 5.13 lbs. of recycled material, and the panel's fill uses 10.22 lbs of recycled material in the cementitious fill. Based on a 3 inch finished floor height, each low profile pedestal assembly uses 1.23 lbs. of recycled content in the steel. By weight, recycled materials constitute 43.2% of the FS200 Low Profile Flooring System: total weight per square foot is 9.60 lbs, of which 4.15 lbs\* is recycled content.

While actual weights and percentages will vary slightly depending on the panel grade selected and the finished floor height, these figures can be used as general guidelines.

For further information on recycled content or how the ASM's Environmental Systems Workplace® can help you achieve points in other LEED categories, please contact your local ASM dealer or email: [jlee@asmproducts.com](mailto:jlee@asmproducts.com), call 843-534-1110, or visit our website at [www.asmproducts.com](http://www.asmproducts.com).

\* The usage rate of pedestals is 1.2 per panel.